Healthy Food Vending Machine

FCV-CEL-10C(V10) Fresh Food Vending Machine - 10.1 inch

TECHNICAL OVERVIEW | FCV-CEL-10C(V10)

The official FCV-CEL-10C(V10) listing shows a six-level elevator cabinet with 10.1-inch touchscreen. Its exact parameter graphic publishes H1945 × W1160 × D870 mm, 300 kg, six drawers and an adjustable 4-25°C range. The gallery describes pushers and a lifting system leading to the lower collection port. HTML separately lists spiral/conveyor/pusher alternatives and a 360-beverage example, while the graphic gives about 300 pieces. These capacity and mechanism presentations remain separate; neither is a mixed-product loading guarantee.

Model summary

FCV catalogue reference	FCV-CEL-10C(V10)
Category	Healthy Food Vending Machine
Screen	10.1 inch
Dimensions	H1945 ×W1160 ×D870 mm
Weight	300kg
Screen	10.1-inch touchscreen
Drawers	6
Temperature	4-25°C adjustable
Supply	100V/240V,50Hz/60Hz

Published source configurations

These source descriptions are kept separate. They do not establish that every value belongs to one supplied unit; the FCV quotation identifies the accepted configuration.

Configuration 1

Source model: FCV-CEL-10C(V10) / 1

Separately published source presentation. This label is not evidence of a chronological production revision or confirmation of the supplied machine.

Quantity	60 slots
Type	Spiral/conveyor /Pusher
Capacity	All beverages 360
Suitable for	Beverages,Snacks,Combo
Dimension	H:1945mmW:1160mmD: 870mm
Screen	10.1 Touch Screen
Voltage	AC 220-240 V,50/60 Hz (readable supply branch)

Power	Refrigerated 520W Noral 40W
Temperature	4-25°C (adjustable)
Payrment methods	Bill,coin,Cashless payment
Support	Credit/DebitCard: VISAMaster CardyAMEXEwallet: Aipay/Momyx/Apple pay/Google Pay/Samsung Pay

Configuration 2

Source model: FCV-CEL-10C(V10) / 2

Separately published source presentation. This label is not evidence of a chronological production revision or confirmation of the supplied machine.

Dimensions	H1945 ×W1160 ×D870 mm
Weight	300kg
Screen	10.1-inch touchscreen
Capacity	About300pieces
Drawers	6
Temperature	4-25°C adjustable
Supply	100V/240V,50Hz/60Hz
Protocol	MDB/DEX



Illustrative FCV-branded concept render. Verify the quoted physical configuration.

Configuration and quotation

Specifications reflect the cited source configuration. Optional accessories and alternative configurations are not included as standard unless explicitly identified in the quotation. Confirm payment hardware, power requirements, installation access and service scope for the intended site. No price, stock quantity, delivery date or certification is implied by this overview.

Configuration details to confirm

The exact parameter graphic provides readable dimensions, 300 kg weight, supply and temperature; malformed HTML values are not silently repaired.

HTML 360-beverage and graphic about-300-piece examples are separate source presentations, not a guaranteed mixed-product load.

The pusher/elevator gallery does not prove that every optional HTML mechanism is installed.

Drawer storage and elevator collection

The matching parameter graphic documents six drawers. The gallery shows pusher and elevator delivery, while the HTML also lists alternative mechanisms.

Storage / equipment zone	Documented source layout
Drawer levels	Six drawers are specified in the exact model-coded parameter graphic.
Product choices	The source lists up to 60 slots. Package width and fit determine usable selections.
Transfer and collection	The exploded diagram labels the lifting system, slots and lower pickup port. A separate poster describes pushers instead of spirals.

- Identify the installed track mechanism and drawer arrangement.
- The selected item transfers to the lifting system.
- Retrieve it from the lower pickup area when delivery is indicated.

Configuration details

Prepared 27 November 2026 for the FCV product catalogue. Confirm the supplied configuration and site requirements with the FCV team before ordering.

Product information

This FCV technical overview describes the listed equipment configuration. The written quotation confirms the machine, accepted product packs, accessories and service scope supplied for your location.

Confirm before purchase

Ask FCV for the exact model and revision, supplied options, current technical sheet, site suitability, warranty, maintenance scope and written commercial terms. Product images, where present, are conceptual branded renders rather than installation evidence.

Website

first-classvending.com