Hot Food Vending Machine

FCV-CFM-8V+FCV-CFN-ZV(V22) Hot Food Vending Machine - 21.5 inch

TECHNICAL OVERVIEW | FCV-CFM-8V+FCV-CFN-ZV(V22)

The combined FCV-CFM-8V+FCV-CFN-ZV(V22) + FCV-CFM-8V+FCV-CFN-ZV(V22) meal cabinet uses XY-axis positioning with a lifting platform. The exact source table lists W 1839 × D 991 × H 1940 mm, 630 kg, AC 220 V and 4000 W. It describes a 21.5-inch display and a packaging-dependent 120-200 capacity range. The illustrated rack has eight horizontal levels; this does not establish a universal per-level product allocation.

Model summary

FCV catalogue reference	FCV-CFM-8V+FCV-CFN-ZV(V22)
Category	Hot Food Vending Machine
Screen	21.5 inch
Dimensions	H1940 × W1839 × D991 mm
Weight	630 kg
Supply	AC220V
Published power	4000W
Display	21.5-inch
Delivery	XY axis movement with lifting platform
Capacity	120-200 (source does not state unit; packaging dependent)

Published source configurations

These source descriptions are kept separate. They do not establish that every value belongs to one supplied unit; the FCV quotation identifies the accepted configuration.

Configuration 1

Source model: FCV-CFM-8V+FCV-CFN-ZV(V22) / 1

A separately published source schedule, not a demonstrated production revision or a promise of the supplied build.

Dimensions	H1940 × W1839 × D991 mm
Weight	630 kg
Supply power	AC220V4000W
Display	21.5-inch HD
Delivery	XY axis moving with lifting platform
Capacity	120-200; unit unstated



Illustrative FCV-branded concept render. Verify the quoted physical configuration.

Configuration and quotation

Specifications reflect the cited source configuration. Optional accessories and alternative configurations are not included as standard unless explicitly identified in the quotation. Confirm payment hardware, power requirements, installation access and service scope for the intended site. No price, stock quantity, delivery date or certification is implied by this overview.

Configuration details to confirm

Combination model is distinct code, do not silently merge with FCV-CFM-8V+FCV-CFN-ZV(V22) alone.

Optional features, certifications and service terms must be confirmed for the quoted configuration.

Aggregate 120-200 capacity is packaging-dependent and is not a per-level loading allocation.

XY-positioned meal storage and lifting platform

The source explicitly describes XY-axis delivery with a lifting platform. Its cutaway shows a stacked meal rack, heating module and illuminated collection area.

Illustrated/source-published configuration only; supplied cabinet configuration must be checked against its documented build.

Storage / equipment zone	Documented source layout
Illustrated meal rack	The isolated rack drawing shows eight horizontal product levels. This is a visual layout observation, not a code-derived or universal shelf count.
Delivery path	An XY-positioned lifting platform transfers the selected meal towards the heating/collection path.

- Select and pay for the meal.
- The source describes XY positioning and lifting transfer from storage.
- Wait for the heating stage and collect when the pickup light indicates.

Configuration details

Prepared 27 November 2026 for the FCV product catalogue. Confirm the supplied configuration and site requirements with the FCV team before ordering.

Product information

This FCV technical overview describes the listed equipment configuration. The written quotation confirms the machine, accepted product packs, accessories and service scope supplied for your location.

Confirm before purchase

Ask FCV for the exact model and revision, supplied options, current technical sheet, site suitability, warranty, maintenance scope and written commercial terms. Product images, where present, are conceptual branded renders rather than installation evidence.

Website

first-classvending.com