Healthy Food Vending Machine

# FCV-CFS-11G(V22)+11V-R Salad & Fresh Food Vending Machine - 21.5 inch

TECHNICAL OVERVIEW | FCV-CFS-11G(V22)+11V-R

This source illustrates a twin-cabinet fresh-food and beverage arrangement sharing a central customer interface. The product-selection graphic explicitly identifies a 21.5-inch touchscreen that also supports advertising and a multi-item shopping cart. It is one interactive display, not evidence of an additional advertising-only screen. Readable HTML lists 140 slots, 840-1120 pieces and 1960×2660×975 mm dimensions, while its power cells state 1400 W refrigerated and 80 W normal. The actual lift illustration describes the transfer mechanism, and the cooling image marks 4°C and 25°C. The weight cell is malformed as 710 KG 5 and cannot be converted to a verified kilogram figure without another source. Product packs and cabinet transfer paths require an accepted loading test; capacity is not a universal refill quantity.

## Model summary

| | |
|---|---|
| FCV catalogue reference | FCV-CFS-11G(V22)+11V-R |
| Category | Healthy Food Vending Machine |
| Screen | 21.5 inch |
| Layout | 140 slots |
| Published capacity | 840-1120 pieces |
| Dimensions | H1960 ×W2660 ×D975 mm |
| Touch screen | 21.5 inch |
| Power | 1400 W refrigerated;80 W normal |
| Temperature | 4-25°C |
| Supported supply branch | AC 220-240 V,50/60 Hz; other branch malformed |
| Mechanism | Elevator/lift transfer illustrated |

## Documented equipment features

- Elevator/lift transfer is illustrated.

- A single 21.5-inch customer touchscreen also supports advertising and multi-item selection.

## Published source configurations

These source descriptions are kept separate. They do not establish that every value belongs to one supplied unit; the FCV quotation identifies the accepted configuration.

## Configuration 1

Source model: FCV-CFS-11G(V22)+11V-R / 1

The explicitly readable 220 V~240V50/60 Hz branch is retained; the malformed 110 V~120 W branch and malformed weight cell are excluded. No value is corrected by guesswork.

| | |
|---|---|
| Layout | 140 slots |
| Published capacity | 840-1120 pieces |
| Dimensions | H1960 ×W2660 ×D975 mm |
| Touch screen | 21.5 inch |
| Power | 1400 W refrigerated;80 W normal |
| Temperature | 4-25°C |
| Supported supply branch | AC 220-240 V,50/60 Hz; other branch malformed |
| Mechanism | Elevator/lift transfer illustrated |




Illustrative FCV-branded concept render. Verify the quoted physical configuration.

## Configuration and quotation

Specifications reflect the cited source configuration. Optional accessories and alternative configurations are not included as standard unless explicitly identified in the quotation. Confirm payment hardware, power requirements, installation access and service scope for the intended site. No price, stock quantity, delivery date or certification is implied by this overview.

## Configuration details to confirm

Malformed weight and lower-voltage branch remain withheld; no corrected kilogram value or 120 V value is invented.

A linked brochure for a separate configuration returns a nontechnical placeholder and does not provide a matching technical schedule for this model.

No per-lane refill quantity, universal product compatibility or food-storage approval is inferred.

## Published storage and dispensing layout

The exact-model HTML lists 140 slots and a product-dependent reference capacity. The source image identifies elevator transfer and a 21.5-inch interactive screen.

| Storage / equipment zone | Documented source layout |
| --- | --- |
| Quantity | 140 slots |

- Match the published drawer, shelf and mechanism fields to the exact supplied version.
- Check actual product dimensions, weight and dispensing clearance in the selected lanes.
- Test delivery and record the accepted loading arrangement; do not infer pieces per lane from the overall capacity.

# Configuration details

Prepared 27 November 2026 for the FCV product catalogue. Confirm the supplied configuration and site requirements with the FCV team before ordering.

## Product information

This FCV technical overview describes the listed equipment configuration. The written quotation confirms the machine, accepted product packs, accessories and service scope supplied for your location.

## Confirm before purchase

Ask FCV for the exact model and revision, supplied options, current technical sheet, site suitability, warranty, maintenance scope and written commercial terms. Product images, where present, are conceptual branded renders rather than installation evidence.

## Website

first-classvending.com