Hot Food Vending Machine

FCV-CMX-ZV(H22)+FCV-CMX-10V Combined Breakfast Vending Machine - 21.5 inch

TECHNICAL OVERVIEW | FCV-CMX-ZV(H22)+FCV-CMX-10V

The model-coded poster identifies a combined FCV-CMX-ZV(H22)+FCV-CMX-10V+FCV-CMX-ZV(H22)+FCV-CMX-10V breakfast machine. It gives H 1965 × W 1645 × D 960 mm, 650 kg, a 21.5-inch display and AC 220 V 4000 W. Horizontal conveyor slots and XY-axis lifting delivery are explicitly described. The photograph illustrates six product levels and a collection opening below the landscape display. HTML uses a shorter H 22 reference, a 22-inch display label and different electrical wording; these remain separately named source statements. No per-level product allocation is established.

Model summary

FCV catalogue reference	FCV-CMX-ZV(H22)+FCV-CMX-10V
Category	Hot Food Vending Machine
Screen	21.5 inch

Published source configurations

These source descriptions are kept separate. They do not establish that every value belongs to one supplied unit; the FCV quotation identifies the accepted configuration.

Configuration 1

Source model: FCV-CMX-ZV(H22)+FCV-CMX-10V / 1

Original page parameters are retained as their own source schedule. Compare any additional layout evidence separately.

Name	Fast Food Vending Machine
Outside Dimensions	H: 1965 mm, W:1645 mm, D: 960 mm
Weight	650 kg
Electricity	AC 100 V/240 V, 50 Hz/60 Hz
Payment System	Bill, Coin, Coin Dispenser(MDB Protocol)
Standard interface	MDB/DEX
Touch Screen	22 inches

Configuration 2

Source model: FCV-CMX-ZV(H22)+FCV-CMX-10V / 2

A separately published source presentation, not proof of a chronological manufacturing revision or supplied build.

Dimensions	H 1965 × W 1645 × D 960 mm
Weight	650 kg
Display	21.5-inch HD

Supply power	AC 220 V 4000 W
Delivery	XY axis moving with lifting platform
Capacity	120-200; source unit unstated



Illustrative FCV-branded concept render. Verify the quoted physical configuration.

Configuration and quotation

Specifications reflect the cited source configuration. Optional accessories and alternative configurations are not included as standard unless explicitly identified in the quotation. Confirm payment hardware, power requirements, installation access and service scope for the intended site. No price, stock quantity, delivery date or certification is implied by this overview.

Configuration details to confirm

The exact combined-model graphic documents 21.5-inch display; 22-inch HTML wording remains a separate source presentation.

Do not infer microwave count or per-level quantities from the suffix or 120-200 capacity range.

Conveyor tracks and XY lifting transfer

The combined-model poster describes horizontal conveyor slots and XY-axis delivery. Its product image is an illustrated layout, not a pack-depth allocation.

Storage / equipment zone	Documented source layout
Complete assembly	The printed identity includes FCV-M048andFCV-M048; the shorter HTML reference is retained separately.
Illustrated product levels	Six merchandise levels are visible. No uniform package depth or shelf capacity is documented.
Delivery	XY-axis movement with a lifting platform and a dedicated collection opening are explicitly shown.

- Match the combined model schedule to the supplied machine.
- Follow the configured selection, payment and heating prompts.
- Collect from the indicated opening when completion is signalled.

Configuration details

Prepared 27 November 2026 for the FCV product catalogue. Confirm the supplied configuration and site requirements with the FCV team before ordering.

Product information

This FCV technical overview describes the listed equipment configuration. The written quotation confirms the machine, accepted product packs, accessories and service scope supplied for your location.

Confirm before purchase

Ask FCV for the exact model and revision, supplied options, current technical sheet, site suitability, warranty, maintenance scope and written commercial terms. Product images, where present, are conceptual branded renders rather than installation evidence.

Website

first-classvending.com