Snack & Drink Vending Machine

FCV-CSC-10C(V22)+10N Modular Snack & Drink Vending Machine

TECHNICAL OVERVIEW | FCV-CSC-10C(V22)+10N

This FCV modular snack-and-drink configuration is based on supplier model FCV-CSC-10C(V22)+10N. The official page contains differing technical tables for screen size, height, weight, shelf arrangement and electrical supply. Obtain the technical sheet for the actual supplied configuration before relying on those values. The branded render illustrates the cabinet finish; it does not resolve the source discrepancies.

Model summary

FCV catalogue reference	FCV-CSC-10C(V22)+10N
Category	Snack & Drink Vending Machine
Screen	Confirm the supplied display configuration

Published source configurations

These source descriptions are kept separate. They do not establish that every value belongs to one supplied unit; the FCV quotation identifies the accepted configuration.

Configuration 1

Source model: FCV-CSC-10C(V22)+10N / 1

A separately published source presentation, not proof of a chronological manufacturing revision or supplied build.

Dimensions	H 1940 × W 2157 × D 790 mm
Weight	410 kg
Selections	About 120
Capacity	About 600 pieces
Drawers	6
Temperature	4-25°C
Supply transcription	415 V/240 V/50 Hz/60 Hz; unresolved, not installation approval
Screen	21.5-inch touch

Configuration 2

Source model: FCV-CSC-10C(V22)+10N / 2

A separately published source presentation, not proof of a chronological manufacturing revision or supplied build.

Dimensions	H 1950 × W 2157 × D 790 mm
Weight	515 kg
Shelves	Standard 6/maximum 7

Choices	50-70 types
Capacity	600 pieces
Temperature	4-25°C
Power	990 Wrefrigerated/120 Wnormal
Supply	AC 110-120 V/220-240 V, 50/60 Hz
Screen	22-inch



Illustrative FCV-branded concept render. Verify the quoted physical configuration.

Configuration and quotation

Specifications reflect the cited source configuration. Optional accessories and alternative configurations are not included as standard unless explicitly identified in the quotation. Confirm payment hardware, power requirements, installation access and service scope for the intended site. No price, stock quantity, delivery date or certification is implied by this overview.

Configuration details to confirm

Same source gives 21.5-inch/22-inch, 410 kg/515 kg, H 1940/H 1950 and different shelves.

415 V/240 V in the first table differs from AC 110-120 V/220-240 V in the second; no typo is corrected by assumption.

ID-age verification is configurable/checkbox content, not proven installed equipment.

Single-cabinet 300-piece artwork is not the full twin-cabinet loading plan.

Twin-cabinet selection and separate collection areas

The source illustrates two storage cabinets using a central selection/payment column and separate lower pickup openings. Photoelectric dispensing detection is described, but a single-cabinet layer diagram must not be treated as proof of the complete twin assembly.

Illustrated/source-published configuration only; supplied cabinet configuration must be checked against its documented build.

Storage / equipment zone	Documented source layout
Two storage sections	The primary photo shows two product display sections, each with its own lower collection opening.
Central control	The illustrated touchscreen/payment column is shared between the two cabinets.
Track detection	Source text describes photoelectric dispensing detection and an anti-theft fetching box.

- Confirm the ordered main/companion cabinet configuration.
- Map each selection to the correct cabinet and its installed track.
- Use the corresponding lower collection opening after the vend indication.

Configuration details

Prepared 27 November 2026 for the FCV product catalogue. Confirm the supplied configuration and site requirements with the FCV team before ordering.

Configuration confirmation

Some equipment configuration details require further confirmation. The catalogue entry is not proof of current FCV stock or a completed site-specific technical acceptance. Unknown fields remain unverified.

Product information

This FCV technical overview describes the listed equipment configuration. The written quotation confirms the machine, accepted product packs, accessories and service scope supplied for your location.

Confirm before purchase

Ask FCV for the exact model and revision, supplied options, current technical sheet, site suitability, warranty, maintenance scope and written commercial terms. Product images, where present, are conceptual branded renders rather than installation evidence.

Website

first-classvending.com