Snack & Drink Vending Machine

FCV-CSC-10C(V32)AC Snack & Drink Vending Machine - 32 inch

TECHNICAL OVERVIEW | FCV-CSC-10C(V32)AC

This wide-display snack and drink cabinet has an explicitly published 32-inch touchscreen. The exact FCV-CSC-10C(V32)AC artwork lists 1945 × 1432 × 790 mm dimensions,300 kg weight, six drawers and 0-25°C refrigeration. The HTML instead identifies FCV-CSC-10C(V32)AC with 1950 × 1433 × 790 mm dimensions,310 kg and 4-25°C. Both schedules remain separate until the supplied revision is identified. The illustrated 60 selections and 300-piece reference do not define a universal mixed-product loading plan.

Model summary

FCV catalogue reference	FCV-CSC-10C(V32)AC
Category	Snack & Drink Vending Machine
Screen	32 inch

Published source configurations

These source descriptions are kept separate. They do not establish that every value belongs to one supplied unit; the FCV quotation identifies the accepted configuration.

Configuration 1

Source model: FCV-CSC-10C(V32)AC / 1

Source-labelled equipment facts. Dispensing mechanisms are alternatives to agree for the supplied unit; no supplier commercial promises or option-checkbox inclusions are adopted.

Material	Metal
Dimensions (H×W×D)	1950 mm / 76.77 in × 1433 mm / 56.42 in × 790 mm / 31.1 in
Weight	310 kg / 683.0 lb
Display Screen	32-inch
Slot Type	Spring/Conveyor/Pusher/Universal
Shelves	Standard 6 / Max. 7
Merchandise Variety	50-70 types(according to products size)
Temperature Range	4-25°C(adjustable)
Storage Capacity	300-800 pcs
Voltage	AC110V~120V/220~240V 50/60Hz
Power (Refrigerated)	442W
Power (Normal)	Normal 44W
Protocol	MDB/DEX

Refrigerant	R1234YF/R290/R513A/134A
Min. Product Size / Weight	100*40*10 mm/20 g
Max. Product Size / Weight	200*150*150 mm/500 g

Configuration 2

Source model: FCV-CSC-10C(V32)AC / 2

This artwork differs from the 1950 mm/310 kg/4-25°C HTML schedule; no independent revision identity is established.

Dimensions (H × W × D)	1945 ×1432 ×790 mm
Weight	300 kg
Selections	Maximum about 60
Storage reference	About 300 pcs, pack dependent
Storage shelves	Six drawers
Temperature	0-25°C adjustable
Supply	100 V /240 V,50/60 Hz
Interface	MDB/DEX



Illustrative FCV-branded concept render. Verify the quoted physical configuration.

Configuration and quotation

Specifications reflect the cited source configuration. Optional accessories and alternative configurations are not included as standard unless explicitly identified in the quotation. Confirm payment hardware, power requirements, installation access and service scope for the intended site. No price, stock quantity, delivery date or certification is implied by this overview.

Configuration details to confirm

Optional features, certifications and service terms must be confirmed for the quoted configuration.

Mechanism, payment hardware/provider compatibility, software licensing, warranty, outdoor equipment and accessories are confirmed for the quoted configuration. Supplier website option ticks are not universal FCV inclusions.

Same page publishes different dimensions, weight, temperature and AC suffix in exact coded artwork versus HTML.

Storage shelves, selected mechanism and collection

The published shelf arrangement and mechanism options describe the cited configuration. They do not establish every option as simultaneously installed or a fixed mixed-product lane load.

Storage / equipment zone	Documented source layout
Slot Type	Spring/Conveyor/Pusher/Universal
Shelves	Standard 6 / Max. 7

- Match the supplied shelf spacing and installed mechanism to the agreed product packs.
- Select and pay using the installed interface; the selected lane releases the product.
- Retrieve the product through the collection opening after delivery.

Configuration details

Prepared 27 November 2026 for the FCV product catalogue. Confirm the supplied configuration and site requirements with the FCV team before ordering.

Configuration confirmation

Some equipment configuration details require further confirmation. The catalogue entry is not proof of current FCV stock or a completed site-specific technical acceptance. Unknown fields remain unverified.

Product information

This FCV technical overview describes the listed equipment configuration. The written quotation confirms the machine, accepted product packs, accessories and service scope supplied for your location.

Confirm before purchase

Ask FCV for the exact model and revision, supplied options, current technical sheet, site suitability, warranty, maintenance scope and written commercial terms. Product images, where present, are conceptual branded renders rather than installation evidence.

Website

first-classvending.com