Snack & Drink Vending Machine

FCV-CSC-8G(V10) Snack & Drink Vending Machine

TECHNICAL OVERVIEW | FCV-CSC-8G(V10)

A glass-front snack-and-drink cabinet with a right-hand customer interface and lower pickup compartment. Supplier artwork identifies six drawers and up to 48 selections. The HTML schedule and artwork disagree on installation height; the HTML screen row says 10-inch while the page image caption says 10.1-inch. Those source presentations are separated below. The linked H5 brochure is a different model and is excluded from this V10 configuration.

Model summary

FCV catalogue reference	FCV-CSC-8G(V10)
Category	Snack & Drink Vending Machine
Screen	Confirm the supplied display configuration
Weight	240 kg
Selections	Up to48
Capacity	Approx.240 pieces, depending on product size
Configuration	Compare separate HTML and V10 artwork schedules

Published source configurations

These source descriptions are kept separate. They do not establish that every value belongs to one supplied unit; the FCV quotation identifies the accepted configuration.

Configuration 1

Source model: FCV-CSC-8G(V10) / 1

HTML schedule lists 10-inch; the page image caption separately says 10.1-inch. Optional features/payment integration are subject to the selected quotation.

Material	Metal
Dimensions (H × W × D)	1950 mm × 885 mm × 790 mm (76.77" × 34.84" × 31.10")
Weight	240 kg (529 lb)
Color	White cabinet with approved FCV line branding (proposed configuration)
Screen	10-inch
Channels	Spring / Conveyor / Pusher / Universal
Universal Channel Supported	Yes
Shelves	Standard 6 / Max. 7
Merchandise Type	48 choices (canned / bottle / box-packed)
Temperature Range	4-25°C / 39.2-77°F (adjustable)

Capacity	Approx. 240 pcs (depending on product size)
Voltage	AC 110-120V / 220-240V, 50/60Hz
Power (Refrigerated)	510W
Power (Normal)	60W
Payment System	Bill, Coin, Cashless Payment
Protocol	MDB / DEX / EXE
Refrigerant	R1234yf / R290 / R513A / R134a
Min. Product Size / Weight	100×40×10 mm / 20g (3.94×1.57×0.39")
Max. Product Size / Weight	200×150×150 mm / 500g (7.87×5.90×5.90")
Enlarged Pickup Port	Yes

Configuration 2

Source model: FCV-CSC-8G(V10) / 2

The coded V10 graphic states1940mm height rather than HTML1950mm. It does not independently print a numeric display size.

Dimensions	H1940 × W885 × D790 mm
Weight	240 kg
Selections	Maximum about 48
Capacity	About 240 pieces, according to product size
Drawers	6
Temperature	4-25°C adjustable
Supply	100V/240V,50Hz/60Hz
Protocol	MDB/DEX



Illustrative FCV-branded concept render. Verify the quoted physical configuration.

Configuration and quotation

Specifications reflect the cited source configuration. Optional accessories and alternative configurations are not included as standard unless explicitly identified in the quotation. Confirm payment hardware, power requirements, installation access and service scope for the intended site. No price, stock quantity, delivery date or certification is implied by this overview.

Configuration details to confirm

Optional features, certifications and service terms must be confirmed for the quoted configuration.

HTML10-inch versus officialimagecaption10.1-inch.

HTML1950mmheight versus V10artwork1940mm.

LinkedPDF is FCV, not this V10 model; excluded rather than transferred.

Published payment, refrigeration and software alternatives describe source options; the supplied FCV configuration and service scope follow the quotation.

Published cabinet and shelf layout

The V10-coded artwork states six drawers with up to 48 choices and a product-dependent approximately 240-piece example. HTML lists six shelves standard/seven maximum. The glass/front, storage stack and lower pickup box are visible in the supplier exploded view.

Storage / equipment zone	Documented source layout
Drawer arrangement	Six drawers in exact V10 artwork; standard 6 / max 7 shelf option in HTML.
Assortment planning	Up to48 choices and approximately 240 pieces are whole-cabinet supplier examples, not a per-tray product plan.
Dispensing and collection	Match the selected channel mechanism, product pack and lower pickup clearance before confirming a loading plan.

- Select the named supplier configuration before planning installation; the published schedules differ.
- Match the six-drawer artwork or the HTML six-standard/seven-maximum shelf option to the quoted cabinet.
- Test actual packs in the selected mechanism and record the accepted load; selection count is not a product-pack quantity.

Configuration details

Prepared 27 November 2026 for the FCV product catalogue. Confirm the supplied configuration and site requirements with the FCV team before ordering.

Configuration confirmation

Some equipment configuration details require further confirmation. The catalogue entry is not proof of current FCV stock or a completed site-specific technical acceptance. Unknown fields remain unverified.

Product information

This FCV technical overview describes the listed equipment configuration. The written quotation confirms the machine, accepted product packs, accessories and service scope supplied for your location.

Confirm before purchase

Ask FCV for the exact model and revision, supplied options, current technical sheet, site suitability, warranty, maintenance scope and written commercial terms. Product images, where present, are conceptual branded renders rather than installation evidence.

Website

first-classvending.com