PPE Vending Machine

# FCV-D720-8C(50SP) PPE Vending Machine - 49 inch

TECHNICAL OVERVIEW | FCV-D720-8C(50SP)

This test-kit vending cabinet combines a full-height 49-inch touchscreen with 48 published product slots. Its model-coded parameter image lists a 1940 × 1005 × 892 mm cabinet, a 320 kg net weight and a 240-piece reference capacity. Refrigerated operation is listed at 458 W, normal operation at 60 W, and the adjustable temperature range at 4-25°C. The large display and enclosed merchandise format support a customer selection journey without a separate glass merchandise window. Test-kit packaging and dispensing suitability should be checked on the selected configuration; the reference capacity does not establish a fixed quantity for every kit.

## Model summary

| | |
|---|---|
| FCV catalogue reference | FCV-D720-8C(50SP) |
| Category | PPE Vending Machine |
| Screen | 49 inch |
| Dimensions | H 1940 × W 1005 × D 892 mm |
| Net weight | 320 kg |
| Touchscreen | 49-inch touchscreen |
| Slots | 48 slots |
| Capacity | 240 pcs |
| Temperature | 4-25°C |
| Refrigerated power | 458 W |
| Normal power | 60 W |

## Published source configurations

These source descriptions are kept separate. They do not establish that every value belongs to one supplied unit; the FCV quotation identifies the accepted configuration.

## Configuration 1

Source model: FCV-D720-8C(50SP) / 1

The source explicitly names 50SP and states a 49-inch touchscreen. Screen size is not inferred from the suffix.

| | |
|---|---|
| Dimensions | H 1940 × W 1005 × D 892 mm |
| Net weight | 320 kg |
| Touchscreen | 49-inch touchscreen |
| Slots | 48 slots |
| Capacity | 240 pcs |

| | |
|---|---|
| Temperature | 4-25°C |
| Refrigerated power | 458 W |
| Normal power | 60 W |




Illustrative FCV-branded concept render. Verify the quoted physical configuration.

## Configuration and quotation

Specifications reflect the cited source configuration. Optional accessories and alternative configurations are not included as standard unless explicitly identified in the quotation. Confirm payment hardware, power requirements, installation access and service scope for the intended site. No price, stock quantity, delivery date or certification is implied by this overview.

## Configuration details to confirm

Published equipment values are transcribed from the source configurations shown here. The quotation identifies the supplied equipment, payment setup, optional hardware and service scope.

## Explore the documented storage and delivery format

The layout below follows the named official source configuration. Variant-specific information remains separate; individual product allocations are not supplied unless documented.

| Storage / equipment zone | Documented source layout |
|---|---|
| Slots | 48 slots |

- Match the supplied cabinet to the FCV-D720-8C(50SP) source configuration.
- Check the documented 48-slot arrangement before assigning test-kit selections.
- Keep the 240-piece capacity attached to its source configuration; no per-slot kit count is supplied.
- Locate the collection opening and the 49-inch customer touchscreen.

# Configuration details

Prepared 27 November 2026 for the FCV product catalogue. Confirm the supplied configuration and site requirements with the FCV team before ordering.

## Product information

This FCV technical overview describes the listed equipment configuration. The written quotation confirms the machine, accepted product packs, accessories and service scope supplied for your location.

## Confirm before purchase

Ask FCV for the exact model and revision, supplied options, current technical sheet, site suitability, warranty, maintenance scope and written commercial terms. Product images, where present, are conceptual branded renders rather than installation evidence.

## Website

first-classvending.com