Healthy Food Vending Machine

FCV-D900V-11L+D900V-ZK(32SP) Salad & Fresh Food Vending Machine - 32 inch

TECHNICAL OVERVIEW | FCV-D900V-11L+D900V-ZK(32SP)

This wide elevator vending cabinet pairs a glass merchandise section with a separate touchscreen control module. The model-coded parameter image and linked brochure identify FCV-D900V-11L+D900V-ZK(32SP), with a 32-inch touchscreen, six drawers and an approximately 240-300-piece capacity. The published cabinet measures 1940 × 1624 × 850 mm and weighs 420 kg. Its parameter schedule lists adjustable 4-8°C refrigeration, 100/240 V supply at 50/60 Hz and MDB/DEX interfaces. The elevator delivery format and wide collection area are shown in the source artwork. The page heading omits one V from the control-module code, so the printed schedule is identified explicitly in the quotation.

Model summary

FCV catalogue reference	FCV-D900V-11L+D900V-ZK(32SP)
Category	Healthy Food Vending Machine
Screen	32 inch
Dimensions H × W × D	1940 × 1624 × 850 mm
Weight	420 kg
Display	32-inch touchscreen
Capacity	About240-300 pieces
Drawers	Six
Temperature	4-8°C
Supply	100/240 V,50/60 Hz
Interfaces	MDB/DEX

Published source configurations

These source descriptions are kept separate. They do not establish that every value belongs to one supplied unit; the FCV quotation identifies the accepted configuration.

Configuration 1

Source model: FCV-D900V-11L+D900V-ZK(32SP) / 1

Dimensions H × W × D	1940 × 1624 × 850 mm
Weight	420 kg
Display	32-inch touchscreen
Capacity	About240-300 pieces
Drawers	Six
Temperature	4-8°C

Supply	100/240 V,50/60 Hz
Interfaces	MDB/DEX

Configuration 2

Source model: FCV-D900V-11L+D900V-ZK(32SP) / 2

Beverage loading	240-300 pieces when loaded with beverages
Power	520Wrefrigerated/40Wnormal



Illustrative FCV-branded concept render. Verify the quoted physical configuration.

Configuration and quotation

Specifications reflect the cited source configuration. Optional accessories and alternative configurations are not included as standard unless explicitly identified in the quotation. Confirm payment hardware, power requirements, installation access and service scope for the intended site. No price, stock quantity, delivery date or certification is implied by this overview.

Configuration details to confirm

Display32inch is explicit in table and actual exploded/parameter graphics; stale numeric-screen warning is incorrect.

Control-module codeD900V-ZK versusD900-ZK and source record-E application suffix need an explicit quoted identity; keep review until reconciled.

Published storage and dispensing details

Review the named source hardware and storage details below. Product packs, usable quantities and the supplied mechanism are confirmed for the selected configuration.

Storage / equipment zone	Documented source layout
Elevator-machine parameter configuration - Capacity	About240-300 pieces
Elevator-machine parameter configuration - Drawers	Six

- Match the source model and mechanism to the quoted cabinet.
- Check actual pack dimensions, loading access and product delivery.
- Record the accepted loading plan after a configuration-specific dispensing test.

Configuration details

Prepared 27 November 2026 for the FCV product catalogue. Confirm the supplied configuration and site requirements with the FCV team before ordering.

Product information

This FCV technical overview describes the listed equipment configuration. The written quotation confirms the machine, accepted product packs, accessories and service scope supplied for your location.

Confirm before purchase

Ask FCV for the exact model and revision, supplied options, current technical sheet, site suitability, warranty, maintenance scope and written commercial terms. Product images, where present, are conceptual branded renders rather than installation evidence.

Website

first-classvending.com