Age-Verification Vending Machine

FCV-NSC-3N(V32) Age-Verification Vending Machine - 32 inch

TECHNICAL OVERVIEW | FCV-NSC-3N(V32)

This listing has an unresolved identity conflict. Its 3N(V32)HTML describes 1835 × 700 × 700 mm,130 kg,a 32-inch touchscreen and five trays withthree spiral slots. The gallery instead contains a coded 2N(V32)-GMtable giving 1850 × 700 × 315 mm,117 kg and five layers withtwo slots. The 3N HTML also states 11 positions per slot and 225 maximum pieces, which do not reconcile. Keep those source schedules separate until the supplied cabinet is identified.

Model summary

FCV catalogue reference	FCV-NSC-3N(V32)
Category	Age-Verification Vending Machine
Screen	32 inch

Published source configurations

These source descriptions are kept separate. They do not establish that every value belongs to one supplied unit; the FCV quotation identifies the accepted configuration.

Configuration 1

Source model: FCV-NSC-3N(V32) / 1

Not merged with differently coded 2N-GMgallery.

Dimensions H × W × D	1835 ×700 ×700 mm
Net/gross weight	130 /180 kg
Screen	32 inch
Supply	AC110-120 V /220-240 V,50/60 Hz
Power	80 W
Structure	Five trays ×three slots;11 positions per slot

Configuration 2

Source model: FCV-NSC-3N(V32) / 2

Publisher identity conflict,not an approved 3Nvariant.

Dimensions H × W × D	1850 ×700 ×315 mm
Weight	117 kg
Structure	Five layers ×two slots
Selections	10
Capacity reference	150 pieces



Illustrative FCV-branded concept render. Verify the quoted physical configuration.

Configuration and quotation

Specifications reflect the cited source configuration. Optional accessories and alternative configurations are not included as standard unless explicitly identified in the quotation. Confirm payment hardware, power requirements, installation access and service scope for the intended site. No price, stock quantity, delivery date or certification is implied by this overview.

Configuration details to confirm

Published per-slot structure multiplies to 165 positions, while source separately claims 225 maximum. Do not present them as a verified loading calculation.

The cited source contains the identified ambiguity; only the displayed, specifically documented values are used. The quotation must identify the supplied configuration.

3N HTMLversus 2N-GMcoded gallery differs on identity,dimensions,weight and slots.

3Nloading arithmetic does not support 225 maximum.

Payment providers,software licences,warranty and accessories require the written quotation; supplier examples are not universal FCV inclusions.

Separately identified 3Nand 2Nlayouts

The page contains differently coded layouts; no uniquely chosen supplied unit.

Storage / equipment zone	Documented source layout
3N HTML	5 trays/3 slots/11 positions;225-piece maximum inconsistent and withheld.
2N-GMgallery	5 layers/2 slots/150 reference underdifferent code.

- Obtain exact cabinet identity and matching technical schedule.

- Confirm actual tray/slot layout.

Configuration details

Prepared 27 November 2026 for the FCV product catalogue. Confirm the supplied configuration and site requirements with the FCV team before ordering.

Configuration confirmation

Some equipment configuration details require further confirmation. The catalogue entry is not proof of current FCV stock or a completed site-specific technical acceptance. Unknown fields remain unverified.

Product information

This FCV technical overview describes the listed equipment configuration. The written quotation confirms the machine, accepted product packs, accessories and service scope supplied for your location.

Confirm before purchase

Ask FCV for the exact model and revision, supplied options, current technical sheet, site suitability, warranty, maintenance scope and written commercial terms. Product images, where present, are conceptual branded renders rather than installation evidence.

Website

first-classvending.com