Hot Food Vending Machine

FCV-ZK-36S Heated Meal Locker Configuration

TECHNICAL OVERVIEW | FCV-ZK-36S

The primary image is a heated meal collection locker with individual transparent cells. Its dimensional diagram states H 1933 × W 1483 × D 302 mm, 36 cells and a 22-inch touchscreen. An adjacent feature graphic describes whole-machine heating to 60°C at room temperature, while the collection diagram shows meals being placed in the cabinet and later retrieved through individual doors. The HTML technical table instead names ZK-36 S at H 1940 × W 1100 × D 1153 mm, 500 kg, six drawers and a 21.5-inch screen. Those are materially different equipment descriptions. The page also mentions microwave heating in generic prose, which does not establish a microwave in the illustrated locker. The public schedules therefore remain separate pending model-matched documentation.

Model summary

FCV catalogue reference	FCV-ZK-36S
Category	Hot Food Vending Machine
Screen	Confirm the supplied display configuration

Published source configurations

These source descriptions are kept separate. They do not establish that every value belongs to one supplied unit; the FCV quotation identifies the accepted configuration.

Configuration 1

Source model: FCV-ZK-36S / 1

A separately identified supplier presentation; not evidence that every schedule describes the same supplied build.

Name	Fast Food Vending Machine
Outside Dimensions	H: 1940 mm, W: 1100 mm, D: 1153 mm
Weight	500 kg
Merchandise type	36 choices(fast food/lunch box/box-packed product)
Storage Capacity	About 36 pcs(according to size of goods)
Interior Storage	6 drawers
Temperature	Can be heated to 60 ° C(without refrigeration)
Electricity	AC 100 V/240 V, 50 Hz/60 Hz
Payment System	Bill, Coin, Coin Dispenser(MDB Protocol)
Standard interface	MDB/DEX
LCD Screen	21.5 inches

Configuration 2

Source model: FCV-ZK-36S / 2

The diagram illustrates a shallow individual-cell locker and conflicts with the HTML cabinet dimensions and six-drawer description. No manufacturing revision is established.

Dimensions	H 1933 × W 1483 × D 302 mm
Compartments	36 individual cells
Display	22-inch touchscreen, stated in diagram
Heating	Whole-machine heating to 60°C at room temperature, stated in adjacent feature graphic



Illustrative FCV-branded concept render. Verify the quoted physical configuration.

Configuration and quotation

Specifications reflect the cited source configuration. Optional accessories and alternative configurations are not included as standard unless explicitly identified in the quotation. Confirm payment hardware, power requirements, installation access and service scope for the intended site. No price, stock quantity, delivery date or certification is implied by this overview.

Configuration details to confirm

HTML and locker diagram differ in dimensions, display, storage architecture and apparent machine format.

Microwave prose, anti-virus wording and security claims are not established equipment inclusions or validated performance.

No default dimensions, mass or numeric display size are adopted until the exact build is identified.

Individual meal cells under assessment

The source diagram illustrates 36 locker cells. It does not substantiate the HTML six-drawer configuration or a microwave appliance.

Storage / equipment zone	Documented source layout
Storage cells	The dimensional drawing states 36 individual cells; meals are retrieved through their respective doors.
Loading and collection	The source workflow shows staff loading meals, identifying collection and the customer taking the meal out.
Heating presentation	The feature graphic describes whole-machine heating to 60°C at room temperature; it is not proof of microwave reheating.

- Resolve which locker or drawer schedule describes the supplied unit.
- Confirm the heating method and model-specific food-handling instructions.
- Check the actual cell opening, packaging and collection workflow.

Configuration details

Prepared 27 November 2026 for the FCV product catalogue. Confirm the supplied configuration and site requirements with the FCV team before ordering.

Configuration confirmation

Some equipment configuration details require further confirmation. The catalogue entry is not proof of current FCV stock or a completed site-specific technical acceptance. Unknown fields remain unverified.

Product information

This FCV technical overview describes the listed equipment configuration. The written quotation confirms the machine, accepted product packs, accessories and service scope supplied for your location.

Confirm before purchase

Ask FCV for the exact model and revision, supplied options, current technical sheet, site suitability, warranty, maintenance scope and written commercial terms. Product images, where present, are conceptual branded renders rather than installation evidence.

Website

first-classvending.com