Snack & Drink Vending Machine

FCV-CSC-10C(V22) Snack & Drink Vending Machine

TECHNICAL OVERVIEW | FCV-CSC-10C(V22)

This snack-and-drink model is represented by three published equipment schedules. The supplied manufacturer brochure describes sixty slots, a 21.5-inch touchscreen and a 1940 × 1275 × 790 mm, 275 kg cabinet. The older application HTML gives 1933 × 1269 × 795 mm, 285 kg and a 22-inch display. A photo-matched white-and-green graphic adds a 1940 × 1269 × 795 mm, 300 kg schedule; its table says 21.5 inches while its feature caption says 22 inches. These values are retained as separate source statements. The brochure lists spiral, conveyor or pusher mechanisms and 300 pieces for an all-beverage load. Neither that beverage reference nor the larger HTML capacity range is a universal mixed-product loading promise.

Model summary

FCV catalogue reference	FCV-CSC-10C(V22)
Category	Snack & Drink Vending Machine
Screen	Confirm the supplied display configuration

Documented equipment features

- The manufacturer brochure lists sixty slots with spiral/conveyor/pusher configurations.
- A separate lower product collection opening is shown in both brochure and application cabinet images.

Published source configurations

These source descriptions are kept separate. They do not establish that every value belongs to one supplied unit; the FCV quotation identifies the accepted configuration.

Configuration 1

Source model: FCV-CSC-10C(V22) / 1

The original manufacturer brochure is supplied separately and its figures are retained as a named configuration.

Dimensions, H × W × D	1940 × 1275 × 790 mm
Weight	275 kg
Display	21.5-inch touchscreen
Slot quantity	60
Mechanism	Spiral / conveyor / pusher
Capacity	300 pieces when loaded entirely with beverages
Temperature	2-25°C adjustable
Power	510 W refrigerated / 40 W normal
Supply	AC 110-120 V / 220-240 V, 50/60 Hz

Configuration 2

Source model: FCV-CSC-10C(V22) / 2

This application-specific HTML schedule differs from the supplied brochure; its original field values are shown separately.

Name	Combo Vending Machine
Outside Dimensions	H: 1933 mm, W:1269 mm, D: 795 mm
Weight	285 kg
Merchandise type	50-70 types(according to products size)
Storage Capacity	About 300-1050 pc (according to size of goods)
Interior Storage	6 drawers
Refrigeration temperature	4-25°C(adjustable)
Electricity	AC 100 V/240 V, 50 Hz/60 Hz
Payment System	Bill, Coin, Coin Dispenser(MDB Protocol)
Standard interface	MDB/DEX
LCD Screen	22 inches

Configuration 3

Source model: FCV-CSC-10C(V22) / 3

The graphic shows the selected white/green application cabinet and gives a third schedule, distinct from both the HTML and supplied brochure.

Dimensions, H × W × D	1940 × 1269 × 795 mm
Weight	300 kg
Slots	60
Display in parameter table	21.5-inch touchscreen
Display in feature caption	22-inch touchscreen
Storage reference	About 300 pieces, depending on product size
Temperature	4-25°C
Supply	100 V/240 V, 50/60 Hz, as printed
Interface	MDB/DEX



Illustrative FCV-branded concept render. Verify the quoted physical configuration.

Configuration and quotation

Specifications reflect the cited source configuration. Optional accessories and alternative configurations are not included as standard unless explicitly identified in the quotation. Confirm payment hardware, power requirements, installation access and service scope for the intended site. No price, stock quantity, delivery date or certification is implied by this overview.

Configuration details to confirm

Each named source schedule describes its own published configuration. Conflicting schedules are not combined into one supplied machine specification.

Payment hardware, payment-provider availability, software licensing and service responsibilities are specified in the quotation. Supplier promotional guarantees and optional-feature ticks are not FCV standard inclusions.

The current source review remains open because the specific discrepancies described in the named schedules have not been resolved for the supplied configuration.

CSC source loading configurations

The supplied brochure and application-specific HTML describe separate loading and equipment schedules.

Storage / equipment zone	Documented source layout
Brochure slot quantity	Sixty slots are specified, with spiral, conveyor or pusher mechanisms.
Brochure beverage loading	The brochure states 300 pieces when loaded entirely with beverages.
Older application layout	The older HTML page describes six drawers and a product-size-dependent capacity range.

Configuration details

Prepared 27 November 2026 for the FCV product catalogue. Confirm the supplied configuration and site requirements with the FCV team before ordering.

Configuration confirmation

Some equipment configuration details require further confirmation. The catalogue entry is not proof of current FCV stock or a completed site-specific technical acceptance. Unknown fields remain unverified.

Product information

This FCV technical overview describes the listed equipment configuration. The written quotation confirms the machine, accepted product packs, accessories and service scope supplied for your location.

Confirm before purchase

Ask FCV for the exact model and revision, supplied options, current technical sheet, site suitability, warranty, maintenance scope and written commercial terms. Product images, where present, are conceptual branded renders rather than installation evidence.

Website

first-classvending.com