Hot Food Vending Machine

FCV-D900-9C(22SP)+WB Meal Vending Machine with Microwave Module

TECHNICAL OVERVIEW | FCV-D900-9C(22SP)+WB

This meal-vending application combines a six-drawer elevator cabinet with a separate three-microwave module. The source parameter panel explicitly identifies FCV-D900-9C(22SP)+WB and gives 1940 mm height, 790 mm depth and 450 kg weight. It prints two width fields, 1275 mm and 557 mm, without defining a combined installation width. The artwork shows pusher release, a lifting platform and lower collection access, while a separate panel illustrates three microwaves with a 3000 W heating label whose scope is unspecified. The parameter table lists about sixty choices and a unitless 240-540 reference; the loading artwork instead lists 54 maximum slots and a 240 beverage reference. These statements remain separate rather than becoming a fixed meal-pack load.

Model summary

FCV catalogue reference	FCV-D900-9C(22SP)+WB
Category	Hot Food Vending Machine
Screen	Confirm the supplied display configuration

Documented equipment features

- Elevator vending cabinet with a separate three-microwave module.
- Pusher dispensing and a lifting platform are explicitly illustrated.
- A separate lower customer collection area is shown.

Published source configurations

These source descriptions are kept separate. They do not establish that every value belongs to one supplied unit; the FCV quotation identifies the accepted configuration.

Configuration 1

Source model: FCV-D900-9C(22SP)+WB / 1

The panel prints two separate W fields and does not identify their combined installation width. The unitless capacity range remains unitless.

Height	1940 mm
First printed W field	1275 mm
Second printed W field	557 mm
Depth	790 mm
Weight	450 kg
Choices	Maximum about 60
Storage reference	About 240-540; units not printed
Drawers	6

Temperature	4-25°C adjustable
Supply	100 V/240 V, 50/60 Hz, as printed
Interface	MDB/DEX

Configuration 2

Source model: FCV-D900-9C(22SP)+WB / 2

The loading artwork publishes a different slot statement and labels its 240 capacity as a beverage reference.

Maximum slots	54
Layers	6
Beverage-reference capacity	240

Configuration 3

Source model: FCV-D900-9C(22SP)+WB / 3

The illustrated three-microwave module is specific to the +WB application. The power figure is not defined as per oven or combined.

Microwaves illustrated	3
Heating label	3000 W; per-oven versus combined scope not stated



Illustrative FCV-branded concept render. Verify the quoted physical configuration.

Configuration and quotation

Specifications reflect the cited source configuration. Optional accessories and alternative configurations are not included as standard unless explicitly identified in the quotation. Confirm payment hardware, power requirements, installation access and service scope for the intended site. No price, stock quantity, delivery date or certification is implied by this overview.

Configuration details to confirm

Published figures remain attached to their named source configuration. Payment equipment, provider availability, software licensing and service responsibilities are specified in the quotation.

Source photographs establish visual provenance. A shared photograph or model-code family does not demonstrate a unique chassis or prove that separate configurations have identical specifications.

The named discrepancies or missing exact-source information described here remain unresolved for the supplied configuration.

Meal storage, elevator and microwave module

The exact +WB application combines product storage and lift delivery with a separately illustrated microwave module.

Storage / equipment zone	Documented source layout
Six storage drawers	Six drawers are specified in the coded parameter panel.
Lift delivery	The artwork illustrates a lifting platform and a separate pickup opening.
Microwave module	Three microwaves are illustrated. The 3000 W label is not assigned to each oven or multiplied into a total.
Loading illustration	The diagram explicitly lists six layers and 54 maximum slots; its 240 figure is a beverage reference.

Configuration details

Prepared 27 November 2026 for the FCV product catalogue. Confirm the supplied configuration and site requirements with the FCV team before ordering.

Configuration confirmation

Some equipment configuration details require further confirmation. The catalogue entry is not proof of current FCV stock or a completed site-specific technical acceptance. Unknown fields remain unverified.

Product information

This FCV technical overview describes the listed equipment configuration. The written quotation confirms the machine, accepted product packs, accessories and service scope supplied for your location.

Confirm before purchase

Ask FCV for the exact model and revision, supplied options, current technical sheet, site suitability, warranty, maintenance scope and written commercial terms. Product images, where present, are conceptual branded renders rather than installation evidence.

Website

first-classvending.com